



◆ SPECIFICATION

Model NO.	LBH30S100	LBH30T100	LBH30S130	LBH30T130	LBH30T130S	LBH30S200	LBH30T200
<b>Camera</b>							
Image Sensor	1/4" Omnivision 1MP CMOS Sensor OV9712S	1/4" Omnivision 1MP CMOS Sensor OV9712S	1/3" SONY 1.3 MP CMOS Sensor IMX238	1/3" Aptina 1.3MP CMOS Sensor AR0130	1/3" SONY 1.3 MP CMOS Sensor IMX238	1/3" SONY 2.4MP CMOS Sensor IMX222	1/3" SONY 2.4MP CMOS Sensor IMX222
Main processor	HI3518C(Hisilicon)	DM365 (TI DaVinci™)	HI3518C(Hisilicon)	DM365 (TI DaVinci™)	DM365 (TI DaVinci™)	HI3516C(Hisilicon)	DM368 (TI DaVinci™)
Resolution	720P		960P			1080P	
Effective Pixels	1280(H)*720(V)		1280(H)*960(V)			1920(H)*1080(V)	
TV System	PAL/NTSC						
Electronic Shutter Time	Auto: PAL 1/50-1/100, 000Sec; NTSC 1/60-1/100, 000Sec						
Sync System	Internal						
Usable Illumination	0.1Lux	0.1Lux	0.01Lux	0.1Lux	0.01Lux	0.01Lux	0.01Lux
S/N Ratio	≥52dB						
Scanning System	Progressive						
Video Output	Network						
<b>Lens</b>							
Focus Length	3.6mm (6mm optional)						
Focus Control	Fixed						
Lens Type	Fixed						
Pixels	2M Pixels					3M Pixels	
<b>Night Vision</b>							
Infrared LED	∅ 5X30PCS						
Infrared Distance	25M						
IR Status	Under 10 Lux By CDS						
IR Power On	CDS Auto Control						
<b>Network</b>							
Ethernet	RJ-45 (10/100Base-T)						
Protocol	IPv4, HTTP, TCP/IP, FTP, NTP, RTSP, UDP, SMTP, DNS, DDNS						
ONVIF	Support ONVIF 2.0						
P2P	YES, Support QR Code						
POE	Optional, Support IEEE 802.3af						
WIFI	N/A						
Video Delay	0.3S (Within the Lan)						
DualStream	Main Stream: 1280*720 Sub Stream: 704*576, 352*288	Main Stream: 1280*960, 1280*720 Sub Stream: 704*576, 352*288				Main Stream: 1920*1080, 1280*720 Sub Stream: 704*576, 352*288	
IE Brower	IE6-11						
Smart Phone	iPhone, iPad, Android, Android Pad						
<b>Camera Features</b>							
Day/Night	Color/ B&W (IR-CUT )						
Compression	H.264/JPEG,Support reloed AVI format.						
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)						
Motion Detection	Support						
Privacy Masking	3 Rectangular Zone						
Recording Mode	NVR/NAS/CMS/Web						
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian						
<b>General</b>							
Housing	Weatherproof , IP66						
Anti-cut Bracket	YES, Cable built-in Bracket						
IR Cut Filter	YES						
Operation Temperature	-10°C ~ +50°C RH95% Max						
Storage Temperature	-20°C ~ +60°C RH95% Max						
Power Source	DC12V±10%, 700mA						
Dimension	142(W)x65(H)x63(D)mm						
Weight	500g						